

PRODUCT FEATURES

- Eight 10/100BaseTX RJ-45 Ports
- Four 100BaseFX Ports, ST or SC Style
- -40°C to 70°C Operating temperature
- Onboard Temperature Sensor
- ESD and Surge Protection Diodes on all Ports
- Auto Sensing 10/100BaseTX, Duplex, and MDIX
- Store-and-forward Technology
- Rugged DIN-Rail Enclosure
- Redundant Power Inputs (10-49VDC)
- Configurable Bi-Color Fault Status LED

FULLY MANAGED FEATURES:

- SNMP v1, v2, v3 and Web Browser Management
- Configuration backup via Optional SD card (NTCD)
- Detailed Ring Map and Fault Location Charting
- N-Ring™ Technology with ~30ms Healing
- N-View™ OPC Monitoring
- N-Link™ Redundant N-Ring Coupling
- IGMP Auto configuration
- 802.1Q tag VLAN and Port VLAN
- 802.1p QoS, Port QoS, and DSCP
- EtherNet/IP™ CIP Messaging
- LLDP (Link Layer Discovery Protocol)
- Port Trunking
- Port Mirroring
- 802.1d, 802.1w, 802.1D RSTP
- DHCP Server, Option 82 relay, Option 61
- Local Port IP Addressing



The N-TRON® 712FX4 compact, fully managed industrial Ethernet switch is housed in a rugged industrial metal enclosure and offers a powerful combination of eight 10/100BaseTX copper ports and four 100Base fiber ports. It is ideally suited for use in industrial and utility applications such as factory floor control networks, electric power substations, wind turbines, wastewater treatment facilities, intelligent traffic control and transportation applications, and any other application where high reliability, superior noise immunity, extreme ruggedness, and extended distance are required.

Remote Monitoring Options - Web browser and N-View OPC (OLE for process control) server software provides configuration and monitoring capability. N-View software easily combines with HMI software to monitor network traffic, alarms, and trends. SNMP is also available for switch link and status monitoring. Status LEDs are configurable to indicate power failure and N-RING status.

N-Ring Technology - N-Ring technology provides expanded ring capacity, detailed fault diagnostics, and fast 30ms healing time. The ring manager validates the integrity of the ring using health check packets and quickly converts the ring to a linear topology within ~30ms when an error is detected. The health status of a ring comprised of all N-Tron fully managed switches may be monitored. A detailed ring map and fault location chart may be accessed by the ring manager's web browser or the OPC server. N-Link™ allows the linking of two N-Rings. Up to 250 fully managed N-TRON switches are supported in an N-Ring topology.

Industrial Specifications - High MTBF, extended shock and vibration specifications, wide operating temperature range and redundant power inputs are standard features.

Ease of Use - The 10/100BaseTX ports are auto sensing and auto configuring. Each copper port is automatically negotiated for maximum speed and performance by default, but can also be hard coded through the user interface. A high speed processor allows wire speed capability on all 10/100BaseTX ports simultaneously.

712FX4 Industrial Ethernet Switch Ordering Information

| | |
|---------------|----------------------------------------------------------------------------------------------------------------|
| 712FX4-XX | Eight 10/100BaseTX Ports, Four Multimode100BaseFX Fiber Optic Ports |
| 712FXE4-XX-YY | Eight 10/100BaseTX Ports, Four Singlemode100BaseFX Fiber Optic Ports |
| NTCD128 | Optional configuration card for backup / restore |
| NTPS-24-1.3 | N-TRON Power Supply - (1.3 Amp @ 24VDC) |
| CPMA-2 | Compact Panel Mount (factory installed option) |
| URMK | Universal Rack Mount Kit |
| Where: | XX = ST or SC YY = 15, 40, or 80 for Singlemode, Blank for Multimode E = Singlemode, and Blank Otherwise |

712FX4 Specifications

Switch Properties

| | |
|--------------------------|-------------------|
| Number of MAC Addresses: | 8000 |
| Aging Time: | Programmable |
| Latency Typical: | 2.6 μ s |
| Switching Method: | Store-and-Forward |

Case Dimensions

| | | |
|-----------------|--------|-----------|
| Height: | 4.3" | (10.8 cm) |
| Width: | 3.1" | (7.9 cm) |
| Depth: | 4.6" | (11.5 cm) |
| Weight (max): | 1.8lbs | (0.8 kg) |
| DIN-Rail Mount: | 35mm | |

Electrical

| | |
|--------------------------|------------------------|
| Redundant Input Voltage: | 10-49 VDC (Regulated) |
| Input Current (max): | 690mA max. @24VDC |
| N-TRON Power Supply: | NTPS-24-1.3 (1.3A@24V) |

Environmental

| | |
|------------------------|-------------------------------|
| Operating Temperature: | -40°C to 70°C |
| Storage Temperature: | -40°C to 85°C |
| Operating Humidity: | 5% to 95% (Non Condensing) |
| Operating Altitude: | 0 to 10,000 ft. |

Shock and Vibration (bulkhead mounted)

| | |
|--------------------|------------------------|
| Shock: | 200g @ 10ms |
| Vibration/Seismic: | 50g, 5-200Hz, Triaxial |

Reliability

| | |
|-------|------------------|
| MTBF: | >2 Million Hours |
|-------|------------------|

Network Media

| | |
|------------|-------------|
| 10BaseT: | >Cat3 Cable |
| 100BaseTX: | >Cat5 Cable |

100 Mb Fiber Transceiver Characteristics

| Fiber Length | 2km* | 15km** | 40km** | 80km** |
|--------------------|---------------|--------------|------------|------------|
| TX Power Min | -19dBm/-14dBm | -15dBm/-7dBm | -5dBm/0dBm | -5dBm/0dBm |
| RX Sensitivity Max | -32dBm | -34dBm | -34dBm | -34dBm |
| Wavelength | 1310nm | 1310nm | 1310nm | 1550nm |

* Multimode Fiber Optic Cable
** Singlemode Fiber Optic Cable

Connectors

| | |
|---------------|--------------------------------------|
| 10/100BaseTX: | Eight (8) RJ-45 Copper Ports |
| 100BaseFX: | Four (4) SC or ST Fiber Duplex Ports |

Recommended Wiring Clearance

| | | |
|--------|----|------------|
| Front: | 4" | (10.16 cm) |
| Side: | 1" | (2.54 cm) |

Regulatory Approvals

FCC: Title 47, Part 15, Subpart B, Class A; ICES-003: Class A; ANSI C63.4

CE: EN 61000-6-2, 4; IEC 61000-4-2, 3, 4, 5, 6, 8, 11

GOST-R Certified, RoHS Compliant

CURRENTLY IN STANDARDS TESTING FOR:

UL/cUL: Hazardous Locations Class I, Div2, Groups A, B, C, D, T4A

Non-hazardous Locations NASI/ISA 12.12.01-2007

Designed to comply with:

IEEE 1613 for Electric Utility Substations

NEMA TS1/ TS2 for Traffic control

IEC-61850




Contact Information

N-TRON Corp.
820 S. University Blvd., Suite 4E
Mobile, AL 36609 USA
TEL: (251) 342-2164
FAX: (251) 342-6353
Website: www.n-tron.com
Email: N-TRON_info@n-tron.com

N-TRON Asia
Unit 1209, Level 12
Chong Hing Finance Center
288 Nanjing Road West
200003 Shanghai
P.R. China
TEL: +86-021-6133-7770
FAX: +86-021-6133-7999

N-TRON Europe GmbH
Alte Steinhäuserstr 19
6330 Cham / Zg Switzerland
TEL: +41 41 7406636
FAX: +41 41 7406637

REV 100205



OPTIONAL COMPACT PANEL MOUNT ASSY.
(P/N: CPMA-2)