



- 1 POST TO WITHSTAND 13 NEWTONS (3 LBS) MINIMUM AXIAL FORCE IN BOTH DIRECTIONS SHOWN WITHOUT DISLODGING.
- 2 TOLERANCES APPLY TO SOLDER SIDE OF BOARD.
- 3 MEASURED AT -A-
- 4 PLASTIC FLASH PERMITTED IN THIS AREA.
- 5 PARTS COMPLY WITH AMP SOLDERABILITY SPEC. NO. 109-11-2.
- 6 ONE HOLE MAY BE UNDERSIZED 0.81-0.89 [0.032-.035] DIA. FOR ASSEMBLY RETENTION ADURING WAVE SOLDERING.
- 7 MATERIAL: HEADER-THERMOPLASTIC POLYESTER
94V-0 (NATURAL)
POST-COPPER ALLOY
FINISH-USE PLATING NOTES 13 & 14 FOR -2 THRU -28
AND NOTES 13 & 15 FOR -32 THRU -58
- 8 COORDINATE DIMENSION APPLIES FROM CENTER OF ACTUAL FEATURE.
- 9 PLASTIC BURRS CAUSED BY CUT-OFF TOOLING ARE PERMITTED WITHIN THE MAXIMUM TOLERANCE ENVELOPE.
- 10 POSTS TO BE MEASURED WHEN STRIP IS HELD FLAT.
- 11 POST MUST WITHSTAND TWO 90° BENDS AGAINST EXTRUSION WITHOUT BREAKING.
- 12 DIMENSION SHOULD BE 2.79-4.06 [0.110-.160] MIN WHEN MATING WITH A MTA-100 CONNECTOR ASSEMBLY OR 2.79-3.05 [0.110-.120] WHEN MATING WITH A CST-100 CONNECTOR ASSEMBLY.
- 13 PLATING: GOLD PLATE AREA, 0.00038[0.000015] GOLD OR 0.00008[0.000003] MIN GOLD FLASH OVER 0.00030 [0.000012] PALLADIUM NICKEL, PER TE CONNECTIVITY'S DISCRETION, ALL SIDES, OVER NICKEL UNDERPLATE, 0.00127 [0.000050] MIN, ALL SIDES AND ENTIRE LENGTH OF POST.
- 14 PLATING: MATTE TIN PLATE AREA, 0.00381-0.00889[0.000150-.000350] THICK, ALL FOUR SIDES 3.56 [0.140] MINIMUM.
- 15 PLATING: MATTE TIN PLATE AREA, 0.00381-0.00889[0.000150-.000350] THICK, ALL FOUR SIDES 3.56 [0.140] MINIMUM.
- 16 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

DIM (L)	NO.OF POSN	ASSEMBLY	LEAD FREE	CONTAINS LEAD	DIM (L)	NO.OF POSN	ASSEMBLY
71.12 [2.800]	28	5-641125-8	SUPERSEDED	X	71.12 [2.800]	28	2-641125-8
68.58 [2.700]	27	5-641125-7			68.58 [2.700]	27	2-641125-7
66.04 [2.600]	26	5-641125-6			66.04 [2.600]	26	2-641125-6
63.50 [2.500]	25	5-641125-5			63.50 [2.500]	25	2-641125-5
60.96 [2.400]	24	5-641125-4			60.96 [2.400]	24	2-641125-4
58.42 [2.300]	23	5-641125-3			58.42 [2.300]	23	2-641125-3
55.88 [2.200]	22	5-641125-2			55.88 [2.200]	22	2-641125-2
53.34 [2.100]	21	5-641125-1			53.34 [2.100]	21	2-641125-1
50.80 [2.000]	20	5-641125-0			50.80 [2.000]	20	2-641125-0
48.26 [1.900]	19	4-641125-9			48.26 [1.900]	19	1-641125-9
45.72 [1.800]	18	4-641125-8			45.72 [1.800]	18	1-641125-8
43.18 [1.700]	17	4-641125-7			43.18 [1.700]	17	1-641125-7
40.64 [1.600]	16	4-641125-6			40.64 [1.600]	16	1-641125-6
38.10 [1.500]	15	4-641125-5			38.10 [1.500]	15	1-641125-5
35.56 [1.400]	14	4-641125-4			35.56 [1.400]	14	1-641125-4
33.02 [1.300]	13	4-641125-3			33.02 [1.300]	13	1-641125-3
30.48 [1.200]	12	4-641125-2	30.48 [1.200]	12	1-641125-2		
27.94 [1.100]	11	4-641125-1	27.94 [1.100]	11	1-641125-1		
25.40 [1.000]	10	4-641125-0	25.40 [1.000]	10	1-641125-0		
22.86 [0.900]	9	3-641125-9	22.86 [0.900]	9	641125-9		
20.32 [0.800]	8	3-641125-8	20.32 [0.800]	8	641125-8		
17.78 [0.700]	7	3-641125-7	17.78 [0.700]	7	641125-7		
15.24 [0.600]	6	3-641125-6	15.24 [0.600]	6	641125-6		
12.70 [0.500]	5	3-641125-5	12.70 [0.500]	5	641125-5		
10.16 [0.400]	4	3-641125-4	10.16 [0.400]	4	641125-4		
7.62 [0.300]	3	3-641125-3	7.62 [0.300]	3	641125-3		
5.08 [0.200]	2	3-641125-2	5.08 [0.200]	2	641125-2		

17 OBSOLETE PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN S. HOOVER 26-JAN-2005		TE Connectivity	
DIMENSIONS: mm [INCHES]		CIR: D. ROSSI 26-JAN-2005			
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVO: D. ROSSI 26-JAN-2005		NAME: MTA-100 HEADER ASSEMBLY, FRICTION LOCK, NOTCHED, .025 SQUARE RIGHT ANGLE POST, .000015 GOLD PLATED	
0 PLC ± 1 PLC ± 2 PLC ± 3 PLC ± 0.13 [0.005] 4 PLC ± ANGLES ±		APPLICATION SPEC		SIZE: A1	
MATERIAL: 7		FINISH: 7		DRAWING NO: 00779	
WEIGHT:		CUSTOMER DRAWING		SCALE: 8:1	
REVISIONS:		SHEET: 1 of 1		REV: V2	